

<b>Pants Fitting Worksheet</b>	<b>Date:</b>	
	<b>Client name</b>	
	<b>Pattern # and Size</b>	

<b>Body Measurement</b>	<b>Waist Circumference</b>	<b>Hip Circumference</b>	<b>Crotch Depth</b>	<b>Crotch Length</b>
<b>Ease Required</b>	1" to 2"(Ease ½+ into waistband.) Loose fit: 1½" Full high hip/abdmn: 2"	Minimum: 1" if pleated 2" if darted _____ larger Hip	¼" if Hip < 37" ¾" if Hip 37-40" 1" if Hip > 40" _____ larger Hip	1" if Hip < 37" 1½" if Hip 37-40" 2" if Hip > 40" _____ larger Hip
<b>Body Meas. + Ease</b>				
<b>Pattern Meas.</b>				
<b>Adjustment Rq'd</b>				

<b>Body Measurement</b>	<b>Hip Depth</b>	<b>Waist to Knee</b>	<b>Waist to Ankle</b>
<b>Ease Required</b>	<b>None</b>	<b>None</b>	<b>None</b>
<b>Pattern Meas.</b>			
<b>Adjustment Rq'd</b>			

**Make Pattern Adjustments in order:**

	<b>Pattern Adjustment</b>	<b>Further Fitting Adj. and notes</b>	<b>Total Adjustment</b>
<b>1. Crotch Depth</b>			
<b>2. Pant Length</b> • Above the Knee • Below the Knee			
<b>3. Waist (½" or less darts and seams)</b>			
<b>4. Hip</b>			
<b>5. Bowleg or Knock Knee(or full inner thigh)</b>	1" to 1½ "		
<b>6. Mark new centre grain line and change pleat placement line.</b>			
<b>7. Flat/Full Seat Wedge (Max 1 ½")</b>			
<b>8. Full Abdomen Wedge (Max 1 ½")</b>			
<b>9. Front Crotch point (Protruding thighs) max ½"</b>			
<b>10. Back Crotch Point For remaining crotch length adj. max 3 ½"</b>			

<b>Further fitting adjustments: Fine tune above adjustments plus (check req'd):</b>															
<b>11. Reshape crotch curve</b>	<b>Notes:</b>														
<b>12. Uneven hip</b> <ul style="list-style-type: none"> <li>• <b>Dart/Pleat Adjustment</b></li> <li>• <b>Waist line Adjustment</b></li> </ul>															
<b>13. Full High Hip</b> <ul style="list-style-type: none"> <li>• <b>Reshape dart(s)</b></li> </ul>															
<b>14. Mark final waistline contour</b>															
After making all pattern adjustments, true pattern lines.	<b>After making pattern adjustments, use the following recommended seam allowances to allow for final fine-tuning of fit.</b> <table border="1"> <tr> <td>Side seams and inseams:</td> <td>1"</td> </tr> <tr> <td>Hem:</td> <td>2"</td> </tr> <tr> <td>Front fly facing:</td> <td>1 ½"</td> </tr> <tr> <td>Front and back crotch seams:</td> <td> <ul style="list-style-type: none"> <li>• 3/8 in crotch area</li> <li>• taper to 5/8" higher up</li> </ul> </td> </tr> <tr> <td>Waistline:</td> <td> <ul style="list-style-type: none"> <li>• 1 - 2" (More if very full seat or tummy.)</li> <li>• Trim after marking final waist seam position.</li> </ul> </td> </tr> <tr> <td>Slant pocket opening:</td> <td>3/8"</td> </tr> <tr> <td>Everywhere else</td> <td>5/8"</td> </tr> </table>	Side seams and inseams:	1"	Hem:	2"	Front fly facing:	1 ½"	Front and back crotch seams:	<ul style="list-style-type: none"> <li>• 3/8 in crotch area</li> <li>• taper to 5/8" higher up</li> </ul>	Waistline:	<ul style="list-style-type: none"> <li>• 1 - 2" (More if very full seat or tummy.)</li> <li>• Trim after marking final waist seam position.</li> </ul>	Slant pocket opening:	3/8"	Everywhere else	5/8"
Side seams and inseams:		1"													
Hem:		2"													
Front fly facing:		1 ½"													
Front and back crotch seams:		<ul style="list-style-type: none"> <li>• 3/8 in crotch area</li> <li>• taper to 5/8" higher up</li> </ul>													
Waistline:		<ul style="list-style-type: none"> <li>• 1 - 2" (More if very full seat or tummy.)</li> <li>• Trim after marking final waist seam position.</li> </ul>													
Slant pocket opening:		3/8"													
Everywhere else	5/8"														
Modify pocket line, pockets, pocket stays to conform to pattern changes.															
Add/adjust to recommended seam allowances.															
For first fitting: For slant pocket, under lap pocket piece or pocket stay and machine baste.															
Machine-baste remaining seams; lightly press back front crotch extensions.															
Fit using ¾" – 1" elastic at waist on top of pant.															
<b>Notes:</b>															